

WARNINGS



- While removing your Bite Switch from your GlassOuse or other devices, pay attention not to damage the wire joining points both on the 3.5mm jack connector and the Bite Switch module parts.
- Do not immerse Bite Switch in water for cleaning purposes. Only clean silicone cover piece after removing it from the Bite Switch module.

BITE SWITCH

Having been tested 100.000 times under 3 tons of pressure, even though Bite Switch is genuinely designed for GlassOuse V1.2, you can connect it to any kind of adapted device offering a mono 3.5mm jack connector plug in for external switch controls since it works with short circuit low signals. Made of durable and solid materials, its flexible wire cable allows you to adjust the switch position according to your needs and it is super lightweight - only 7.2 grams.

Bite Switch's silicone cover piece is made of certified non-carcinogenic waterproof material and has a RoHS certificate. With its simple removal, Bite Switch cover can be cleaned easily and it offers a hygienic everyday use. To clean the silicone cover, remove it carefully and rinse it in water or use a damp cloth. Please be sure that the cover piece is fully dried inside before putting it back onto the Bite Switch tip.



SWITCH CONNECTION

1. Plug Bite Switch to your device via mono 3.5mm jack connector.
2. Adjust the position of Bite Switch wire until you feel comfortable enough to do clicking action.
3. Press the switch to activate your device.

GS01 - BITE SWITCH

Length: 183mm x Width: 18.2mm x Thickness: 10.5mm

Weight: 7.2g

Cable Length: 110mm

Activation Force: 300-g

DEVICE

